

PF6055 PakFORCE 2.5 CU. YD. STATIONARY COMPACTOR

MODEL NUMBER.

PF6055

WASTEC Rating Size	2.09 cu. yd.
Clear Top Opening -	Length..... 55"
	Width..... 59-1/2"
Ram Penetration	16"
Chamber Length	56"
Ram Face -	Height..... 29"
	Width..... 60"
Cylinder Stroke	72"
Cylinder Bore	6"
Cylinder Rod Diameter	4"
Discharge Opening -	Height..... 39"
	Width..... 61-1/2"
Ground Height	16"
Scale Weight	Approx.5,400 lbs.
Cycle Time	51.3
Pump Size	10.3 GPM
Motor Size	10 HP
Operating Pressure -	Normal..... 1950 PSI
	Maximum..... 2250 PSI
Force Rating -	Normal..... 31.7/55,200
	Maximum..... 36.6/63,700
Chamber Sides	1/4" Plate
Chamber Floor	1/2" Plate
Ram Top	1/4" Plate
Ram Sides	1/4" Plate
Ram Floor	1/4" Plate
Ram Face	1/2" Plate
Top Cover	Floor Plate..... 12 Ga.
Volume Displacement Rate	146 cu. yd. per hr.

STANDARD FEATURES

- Solid State Control System
- External Power Plant
- UL & Canadian UL Listed Industrial Control Panel
- 10 HP, 208/230/460 Volt, 3 Phase Continuous Duty Motor
- 37 Gallon Capacity Oil Tank
- 40 Micron Air Filter
- 200 Mesh Suction Filter in Reservoir
- Oil Level Sight Gauge with Thermometer
- 40 G.P.M. Regenerative Hydraulic Control Valve
- 3/4 Full Light (1550 PSI)
- Container Full Light (1950 PSI)
- Hold to Operate Mode
- Hold to Operate Extend/Auto Retract Mode
- 2 - 8 Multicycle Modes
- Ram Stop Extended Mode
- Operator's Controls on 15' Flexible Conduit
- Claw Type Grab Hooks
- Replaceable Nylon Ram Guides
- Floor Plate Walk-On Deck
- 5 Retaining Teeth
- Finish Paint Any Standard Galbreath Color
- 2 Year Limited Warranty

OPTIONAL FEATURES

- Electro-Mechanical Power Plant
- Weather Cover for Power Plant
- Internal Power Plant
- Pressure Gauge
- 500 Watt Oil Heater
- Photoelectric Eye
- Low Oil/High Temperature Shut Off Sensor
- Interlock Switch On 30' Flexible Conduit
- Hauler's Controls on 15' Flexible Conduit
- Hoppers
- Drive-On Deck
- Chutes
- 15 HP With 13 GPM Power Plant
- 20 HP With 16 GPM Power Plant

